

31 Fiberglass Membrane

DESCRIPTION:

Karnak #31 Fiber Glass Membrane is a waterproofing fabric woven entirely of fiberglass yarn. It is ideal for use with cold application cements and coatings, and being of high flexibility, conforms to all contours and bends as required in general roofing and waterproofing maintenance.

FEATURES, BENEFITS AND ADVANTAGES:

- Contour flexibility without cracking
- High tensile strength
- Will not mildew, rot or decay
- Acid and alkali resistant

SPECIFICATIONS:

ASTM D-1668, Fed. Spec. HH-C466b.

PHYSICAL PROPERTIES:

(oz. /sq. /yd):	2.00
(lbs./36" x 150' roll):	6.5
Thread Count per Inch:	20 x 10

TENSILE STRENGTH:

Warp (lbs./lineal inch):	75
Fill (lbs./lineal inch):	75

COMPATIBILITY:

Karnak #31 Fiber Glass Membrane is treated with a synthetic resin in the proper balance to give complete compatibility with asphalt or tar and all accepted waterproofing and coating compounds.

Weight and tensile strength figures are nominal values. Production variations limited to plus or minus 10% of these figures.

PACKAGING:

ROLL SIZE	ROLLS/CARTON
36" X 150'	6
18' X 150'	6
12' X 150'	6
9" X 150'	12
6" X 150'	12
4" X 150'	18

Please see page 222 for additional mold and safety information.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>